



Standard Single Strand Roller Chain For Bicycle

		Dimensions (mm)							
Chain No	Pitch	Roller Link Width (minimum)	Roller Diameter	Inner Plate		Pin Diameter	Over All Width		Minimum Tensile Strength
				Thickness	Width		F	G	
	P	W	R	T	H	D	F	G	kgf
UG	12.700	2.38	7.77	1.00	8.34	3.60	7.74	-	820
410	12.700	3.45	7.77	0.90	9.82	3.60	9.35	10.85	820

Standard Single Strand Roller Chain For Motorcycle

415H	12.700	4.75	7.77	1.45	12.00	3.96	13.05	14.55	1,600
420	12.700	6.25	7.77	1.45	12.00	3.96	14.80	16.20	1,600
420SL	12.700	6.25	7.77	1.30	12.00	3.96	14.35	16.20	1,600
420SBZ1	12.700	6.25	7.77	1.45	12.00	3.96	14.80	16.20	1,650
428	12.700	7.85	8.51	1.45	12.00	4.50	16.85	18.85	1,800
428H	12.700	7.85	8.51	2.00	11.80	4.50	18.75	20.30	2,100
520	15.875	6.25	10.16	2.00	15.00	5.08	17.25	18.45	2,700
525	15.875	7.90	10.16	2.00	15.00	5.08	18.70	19.90	2,700
530	15.875	9.60	10.16	2.00	15.00	5.08	20.45	21.65	2,700
520H	15.875	6.25	10.16	2.30	15.00	5.24	18.80	19.70	3,300
525H	15.875	7.90	10.16	2.30	15.00	5.24	20.35	21.25	3,300
530H	15.875	9.60	10.16	2.30	15.00	5.24	22.00	22.90	3,300
630	19.050	9.65	11.91	2.30	17.80	5.95	22.20	23.55	3,700

Standard Single Strand Roller Chain For Heavy Duty Motorcross

520HCR	15.875	6.25	10.16	2.30	15.00	5.24	18.80	19.70	3,600
--------	--------	------	-------	------	-------	------	-------	-------	-------

Standard Single Strand Roller Chain For Industry

40	12.700	8.00	7.95	1.45	12.00	3.96	16.25	17.70	1,600
50	15.875	9.60	10.16	2.00	15.00	5.08	20.45	21.65	2,700
60	19.050	12.90	11.91	2.30	17.80	5.95	25.45	26.80	3,700
80	25.400	16.10	15.88	3.10	24.00	7.93	32.40	33.90	6,600

Remark :